

LV429440



Features:

- Reliable action and quick response.
- Compact structure and strong adaptability.
- Safe and stable, with a long maintenance free cycle.

Common accessories				
Compact NSX100/160/250	Voltage (V)	Frequency (HZ)	MT100/160 Part Number	MT250 Part Number
AC	40-60	50/60	LV429440	LV431548
	110-130	50/60	LV429433	LV431540
	220-240	50/60	LV429435	LV431542
	208-277	60	LV429435	LV431542
	380-415	50/60	LV429434	LV431541
	440-480	60	LV429434	LV431541
DC	24-30	/	LV429436	LV431543
	48-60	/	LV429437	LV431544
	110-130	/	LV429438	LV431545
	250	/	LV429439	LV431546

LV429385



Features:

- Accurate release, sensitive response.
- Original adaptation, strong compatibility.
- Industrial durability, stable operation.

Compact NSX100/160/250	Voltage (V)	Frequency (HZ)	MX Part Number	MN Part Number
AC	24	50/60	LV429384	LV429404
	48	50/60	LV429385	LV429405
	110-130	50/60	LV429386	LV429406
	220-240	50/60	LV429387	LV429407
	208-277	50/60	/	/
	380-415	/	LV429388	LV429408
	440-480	/	/	/
DC	12V	/	LV429382	LV429402
	24V	/	LV429390	LV429410
	30V	/	LV429391	LV429411
	48V	/	LV429392	LV429412
	60V	/	/	LV429403
	125V	/	LV429393	LV429413
	250V	/	LV429394	LV429414

LV432641



Features:

- Accurate release, sensitive response.
- Original adaptation, strong compatibility.
- Industrial durability, stable operation.

Compact NSX400/630	Voltage (V)	Frequency (HZ)	MT400-630 Part Number
AC	48-60	50/60	LV432639
	110-130	50/60	LV432640
	220-240	50/60	LV432641
	208-277	60	LV432641
	380-415	50	LV432642
	440-480	60	LV432647
DC	24-30	/	LV432643
	48-60	/	LV432644
	110-130	/	LV432645
	250	/	LV432646

LV432597



Features:

- Original adaptation, strong compatibility.
- Stable and reliable leakage protection.
- Industrial grade durable design.

Compact NSX100/160/250	Purpose	3p Part Number	4p Part Number
AC/DC	ME is used for NSX100/160 (200 to 440V)	LV429212	LV429213
	MH is used for NSX100/160 (220 to 440V)	LV429210	LV429211
	MH is used for NSX250 (220 to 440 V)	LV431535	LV431536
	MH is used for NSX100/160 (440 to 550V)	LV429215	LV429216
	MH is used for NSX250 (440 to 550 V)	LV431533	LV431534



LV429337



Features:

- Reliable action and quick response.
- Compact structure and strong adaptability.
- Safe and stable, with a long maintenance free cycle.

LV429382



Features:

- Remote tripping, quick response.
- Original factory adaptation, strong universality.
- Solid workmanship and stable working conditions.

LV432597



Features:

- Original factory precise adaptation.
- Safe and convenient operation.
- High strength, durable, and resistant to manufacturing.

Compact NSX100/160/250	Purpose	Part Number
AC/DC	OF or SD or SDE(*) or SDV	29450
	OF or SD or SDE(*) or SDV is low	29452
	(*) SDE adapter for TM release	LV429451
	SDx module 24/415 V AC/DC	LV429532
	Standard black handle	LV429337
	Red handle yellow cover	LV429339
	Accessories for MCC	LV429341
	Accessories for cnomo	LV429342
	Standard extended rotary handle	LV429338
	Red handle yellow cover	LV429340
	Retractable handle for retractable equipment	LV429343

Compact NSX400/630	Voltage (V)	Frequency (HZ)	MX Part Number	MN Part Number
AC	24	50/60	LV429384	LV429404
	48	50/60	LV429385	LV429405
	110-130	50/60	LV429386	LV429406
	220-240	50/60	LV429387	LV429407
	208-277	50/60	/	/
	380-415	/	LV429388	LV429408
	440-480	/	/	/
DC	12	/	LV429382	LV429402
	24	/	LV429390	LV429410
	30	/	LV429391	LV429411
	48	/	LV429392	LV429412
	60	/	/	LV429403
	125	/	LV429393	LV429413
	250	/	LV429394	LV429414

Compact NSX400/630	Purpose	MT400-630 Part Number
AC/DC	Standard black handle	LV432597
	Red handle yellow cover	LV432599
	Accessories for MCC	LV432606
	Accessories for cnomo	LV432602
	Standard extended rotary handle	LV432598
	Red handle yellow cover	LV432600
	Retractable handle for retractable equipment	LV432603
	Handle indicating accessories	LV432605
		LV429346

