

ATS22 soft starter



Features:

- Built in bypass contactor, compact structure.
- Simple intelligent debugging, comprehensive protection.
- Wide voltage adaptation, high cost-effectiveness.

Power supply voltage parameters	Model	Rated power of motor	Amp
Q(220-440) AC400V	ATS22D17Q	7.5kw	17A
	ATS22D32Q	15KW	32A
	ATS22D47Q	22KW	47A
	ATS22D62Q	30KW	62A
	ATS22D75Q	37KW	75A
	ATS22D88Q	45KW	88A
	ATS22C11Q	55KW	110A
	ATS22C14Q	75KW	140A
	ATS22C17Q	90KW	170A
	ATS22C21Q	110KW	210A
	ATS22C25Q	132KW	250A
	ATS22C32Q	160KW	320A
	ATS22C41Q	220KW	410A
	ATS22C48Q	250KW	480A
	ATS22C59Q	315KW	590A
S6(220-600) AC400V	ATS22D17S6	7.5kw	17A
	ATS22D32S6	15KW	32A
	ATS22D47S6	22KW	47A
	ATS22D62S6	30KW	62A
	ATS22D75S6	37KW	75A
	ATS22D88S6	45KW	88A
	ATS22C11S6	55KW	110A
	ATS22C14S6	75KW	140A
	ATS22C17S6	90KW	170A
	ATS22C21S6	110KW	210A
	ATS22C25S6	132KW	250A
	ATS22C32S6	160KW	320A
	ATS22C41S6	220KW	410A
	ATS22C48S6	250KW	480A
	ATS22C59S6	315KW	590A
S6U(110-600) AC400V	ATS22D17S6	7.5kw	17A
	ATS22D32S6	15KW	32A
	ATS22D47S6	22KW	47A
	ATS22D62S6	30KW	62A
	ATS22D75S6	37KW	75A
	ATS22D88S6	45KW	88A
	ATS22C11S6	55KW	110A
	ATS22C14S6	75KW	140A
	ATS22C17S6	90KW	170A
	ATS22C21S6	110KW	210A
	ATS22C25S6	132KW	250A
	ATS22C32S6	160KW	320A
	ATS22C41S6	220KW	410A
	ATS22C48S6	250KW	480A
	ATS22C59S6	315KW	590A



PSE soft starter



Features:

- Built in bypass contactor,energy-saving design.
- Full dimensional motor protection,high reliability.
- Minimalist debugging,universal adaptation.

Power supply voltage parameters	Model	Rated power of motor	Amp
RATED 208-600V	PSR3-600-11	2.2KW	3.9A
	PSR6-600-11	4KW	6.8A
	PSR9-600-11	4KW	9A
	PSR12-600-11	5.5KW	12A
	PSR16-600-11	7.5KW	16A
	PSR25-600-11	15KW	25A
	PSR30-600-11	18.5KW	30A
	PSR37-600-11	22KW	37A
	PSR45-600-11	30KW	45A
	PSR60-600-11	37KW	60A
	PSR72-600-11	45KW	72A
	PSR85-600-11	55KW	85A
	PSR105-600-11	55KW	105A
RATED 208-690V	PSTX30-690-70	25KW	30A
	PSTX37-690-70	30KW	37A
	PSTX45-690-70	37KW	45A
	PSTX60-690-70	55KW	60A
	PSTX72-690-70	59KW	72A
	PSTX85-690-70	75KW	85A
	PSTX105-690-70	90KW	106A
	PSTX142-690-70	132KW	143A
	PSTX170-690-70	160KW	171A
	PSTX210-690-70	184KW	210A
	PSTX250-690-70	220KW	250A
	PSTX300-690-70	257KW	300A
	PSTX370-690-70	355KW	370A
	PSTX470-690-70	450KW	470A
	PSTX570-690-70	560KW	570A
	PSTX720-690-70	710KW	720A
	PSTX840-690-70	800KW	840A
	PSTX1050-690-70	1000KW	1050A
	PSTX1250-690-70	1200KW	1250A

PSR Compact soft starter



Features:

- Extremely compact, with built-in bypass.
- Minimalist debugging, high cost-effectiveness.
- High reliability protection, wide voltage adaptation.

Power supply voltage parameters	Model	Rated power of motor	Amp
RATED 400V MAX600V	PSR3-600-70 400V	1.5KW	3.9A
	PSR6-600-70 400V	3KW	6.8A
	PSR9-600-70 400V	4KW	9A
	PSR12-600-70 400V	5.5KW	12A
	PSR16-600-70 400V	7.5KW	16A
	PSR25-600-70 400V	11KW	25A
	PSR30-600-70 400V	15KW	30A
	PSR37-600-70 400V	18.5KW	37A
	PSR45-600-70 400V	22KW	45A
	PSR60-600-70 400V	30KW	60A
	PSR72-600-70 400V	37KW	72A
	PSR85-600-70 400V	45KW	85A
	PSR105-600-70 400V	55KW	105A
RATED 500V MAX600V	PSR3-600-70 500V	2.2KW	3.9A
	PSR6-600-70 500V	4KW	6.8A
	PSR9-600-70 500V	4KW	9A
	PSR12-600-70 500V	5.5KW	12A
	PSR16-600-70 500V	7.5KW	16A
	PSR25-600-70 500V	15KW	25A
	PSR30-600-70 500V	18.5KW	30A
	PSR37-600-70 500V	22KW	37A
	PSR45-600-70 500V	30KW	45A
	PSR60-600-70 500V	37KW	60A
	PSR72-600-70 500V	45KW	72A
	PSR85-600-70 500V	55KW	85A
	PSR105-600-70 500V	55KW	105A

PSTX60-600-70 400V



Features:

- Integrated hardcore solution.
- Wide pressure intelligent control.
- Full dimensional protection+worry free operation.

Power supply voltage parameters	Model	Rated power of motor	Amp
RATED 400V MAX600V	PSTX30-600-70 400V	15KW	30A
	PSTX37-600-70 400V	18.5KW	37A
	PSTX45-600-70 400V	22KW	45A
	PSTX60-600-70 400V	30KW	60A
	PSTX72-600-70 400V	37KW	72A
	PSTX85-600-70 400V	45KW	85A
	PSTX105-600-70 400V	55KW	106A
	PSTX142-600-70 400V	75KW	143A
	PSTX170-600-70 400V	90KW	171A
	PSTX210-600-70 400V	110KW	210A
	PSTX250-600-70 400V	132KW	250A
	PSTX300-600-70 400V	160KW	300A
	PSTX370-600-70 400V	200KW	370A
	PSTX470-600-70 400V	250KW	470A
	PSTX570-600-70 400V	315KW	570A
	PSTX720-600-70 400V	400KW	720A
	PSTX840-600-70 400V	450KW	840A
	PSTX1050-600-70 400V	560KW	1050A
	PSTX1250-600-70 400V	710KW	1200A
RATED 500V MAX600V	PSTX30-600-70 500V	18.5KW	30A
	PSTX37-600-70 500V	22KW	37A
	PSTX45-600-70 500V	25KW	45A
	PSTX60-600-70 500V	37KW	60A
	PSTX72-600-70 500V	45KW	72A
	PSTX85-600-70 500V	55KW	85A
	PSTX105-600-70 500V	75KW	106A
	PSTX142-600-70 500V	90KW	143A
	PSTX170-600-70 500V	110KW	171A
	PSTX210-600-70 500V	132KW	210A
	PSTX250-600-70 500V	160KW	250A
	PSTX300-600-70 500V	200KW	300A
	PSTX370-600-70 500V	257KW	370A
	PSTX470-600-70 500V	315KW	470A
	PSTX570-600-70 500V	400KW	570A
	PSTX720-600-70 500V	500KW	720A
	PSTX840-600-70 500V	600KW	840A
	PSTX1050-600-70 500V	730KW	1050A
	PSTX1250-600-70 500V	880KW	1200A

SIEMENS

SOFT STARTERS

3RW40 soft starter



Features:

- Equipped with a bypass, saving cabinet and electricity.
- One click debugging, full dimensional protection.
- Compatible across the entire range, with high cost-effectiveness.

Power supply voltage parameters	Model	Rated power of motor	Amp
AC200-480V	3RW4024-2BB04	5.5KW	12.5A
	3RW4026-2BB04	11KW	25A
	3RW4027-2BB04	15KW	32A
	3RW4028-2BB04	18.5KW	38A
	3RW4036-2BB04	22KW	45A
	3RW4037-2BB04	30KW	63A
	3RW4038-2BB04	37KW	72A
	3RW4046-2BB04	45KW	80A
	3RW4047-2BB04	55KW	106A
	3RW4055-2BB34	75KW	134A
	3RW4056-2BB34	90KW	162A
	3RW4073-2BB34	132KW	230A
	3RW4074-2BB34	160KW	280A
	3RW4075-2BB34	200KW	365A
	3RW4076-2BB34	250KW	432A
AC200-460V	3RW4024-2BB05	5.5KW	12.5A
	3RW4026-2BB05	11KW	25A
	3RW4027-2BB05	15KW	32A
	3RW4028-2BB05	18.5KW	38A
	3RW4036-2BB05	22KW	45A
	3RW4037-2BB05	30KW	63A
	3RW4038-2BB05	37KW	72A
	3RW4046-2BB05	45KW	80A
	3RW4047-2BB05	55KW	106A
	3RW4055-2BB35	75KW	134A
	3RW4056-2BB35	90KW	162A
	3RW4073-2BB35	132KW	230A
	3RW4074-2BB35	160KW	280A
	3RW4075-2BB35	200KW	356A
	3RW4076-2BB35	250KW	432A

3RW30 soft starter



Features:

- Ultra small size, saving cabinet and electricity.
- DC24V adaptation, zero threshold debugging.
- Low power exclusive, full cost-effectiveness.

Power supply voltage parameters	Model	Rated power of motor	Amp
AC200-480V	3RW3013-1BB04	1.5KW	3.6A
	3RW3014-1BB04	3KW	6.5A
	3RW3016-1BB04	4KW	9A
	3RW3017-1BB04	5.5KW	12.5A
	3RW3018-1BB04	7.5KW	17.6A
	3RW3026-1BB04	11KW	25A
	3RW3027-1BB04	15KW	32A
	3RW3028-1BB04	18.5KW	38A
	3RW3036-1BB04	22KW	45A
	3RW3037-1BB04	30KW	63A
	3RW3038-1BB04	37KW	72A
	3RW3046-1BB04	45KW	80A
	3RW3047-1BB04	55KW	106A



NJR2 soft starter



Features:

- High cost-effectiveness, full power coverage.
- Large screen intuitive debugging, full dimensional protection.
- Wide voltage adaptation, compatibility with operating conditions.

Power supply voltage parameters	Model	Rated power of motor	Amp
380v	NJR2-7.5D	7.5KW	15A
	NJR2-11D	11KW	22A
	NJR2-15D	15KW	29A
	NJR2-18.5D	18.5KW	36A
	NJR2-22D	22KW	42A
	NJR2-30D	30KW	57A
	NJR2-37D	37KW	70A
	NJR2-45D	45KW	84A
	NJR2-55D	55KW	103A
	NJR2-75D	75KW	140A
	NJR2-90D	90KW	167A
	NJR2-110D	110KW	207A
	NJR2-132D	132KW	248A
	NJR2-160D	160KW	300A
	NJR2-185D	185KW	349A
	NJR2-220D	220KW	404A
	NJR2-250D	250KW	459A
	NJR2-280D	280KW	514A
	NJR2-315D	315KW	579A

