

LR9G630



Features:

- Ultra high current coverage. Fully functional electronic
- protection. Direct insertion installation,
- maintenance free.

Mini-Contactors with AC Operating Coils											
Maximum Horsepower Ratings								Thermal Setting (A)	GV2ME push button	GV2/3P rotary handle	
Single-Phase			Three-Phase						Catalog Number	Catalog Number	
115V	200V	230V	115V	200V	230V	460V	575V				
/	/	/	/	/	/	/	/	/	0.10-0.16	GV2ME01	GV2P01
/	/	/	/	/	/	/	/	/	0.16-0.25	GV2ME02	GV2P02
/	/	/	/	/	/	/	/	/	0.25-0.40	GV2ME03	GV2P03
/	/	/	/	/	/	/	/	/	0.40-0.63	GV2ME04	GV2P04
/	/	/	/	/	/	/	/	1/2	0.63-1	GV2ME05	GV2P05
/	/	1/10	/	/	/	3/4	3/4		1-1.6	GV2ME06	GV2P06
/	1/6	1/6	/	1/2	1/2	1	1.5		1.6-2.5	GV2ME07	GV2P07
1/8	1/4	1/3	/	3/4	3/4	2	3		2.5-4	GV2ME08	GV2P08
1/4	1/2	1/2	3/4	1	1.5	3	5		4-6.3	GV2ME10	GV2P10
1/2	1	1.5	1	2	3	5	7.5		6-10	GV2ME14	GV2P14
3/4	2	2	2	3	3	10	10		9-14	GV2ME16	GV2P16
1	2	3	2	5	5	10	15		13-18	GV2ME20	GV2P20
1.5	3	3	3	5	7.5	15	20		17-23	GV2ME21	GV2P21
2	/	/	/	7.5	7.5	15	20		20-25	GV2ME22	GV2P22
2	5	5	5	7.5	10	20	25		24-32	GV2ME32	GV2P32
1/2	/	1.5	/	3	3	7.5	10		9-13	/	GV3P13
3/4	/	2	/	3	5	7.5	10		12-18	/	GV3P18
1.5	/	3	/	5	7.5	15	20		17-25	/	GV3P25
2	/	3	/	7.5	7.5	20	25		23-32	/	GV3P32
3	/	5	/	10	10	25	30		30-40	/	GV3P40
3	/	7.5	/	10	10	30	40		37-50	/	GV3P50
3	/	10	/	15	15	40	50		48-65	/	GV3P65
5	/	15	/	20	25	50	60		62-73	/	GV3P73

