

Easy301-0808TN RS485



Features:

- Simplified and practical IO configuration.
- Ultra thin volume+rail installation.
- Domestic stable and reliable.

Model	Specification
Easy301-0808TN RS485	8 ID 8OD PLC RS485
Easy302-0808TN RS485	8 ID 8OD PLC RS485
Easy320-0808TN Ethernet	8 ID 8OD PLC Ethernet

GE20-2AD1DA-I



Features:

- Accurate analog quantity acquisition.
- Plug and play expansion is convenient.
- Industrial grade reliable and durable.

Model	Specification
GE20-2AD1DA-I	2 Input 1output Analog
GL20-4AD	4 Way Analog Input Module
GL20-4DA	4 Way Analog Output Module
GL20-4PT	4 Way thermal resistor Module
GE20-4DI	4 Way Digital Module
GL20-0808ETN	8 Way Digital I/O
GL20-0800END	8 Way input
GL20-0008ETN	8 Way output
GL20-1600END	16 Way input

MD600S-2S010B-INT



Features:

- Single phase 220V compact design.
- Built in braking unit, smooth start stop and fast response.
- Stable, reliable, easy to debug.

Model	Specification
2.2KW	MD600S-2S010B-INT
0.37KW	MD600S-4T1R6-INT
0.75KW	MD600S-4T2R3-INT
1.5KW	MD600S-4T4R8-INT
2.2KW	MD600S-4T5R5B-INT
4KW	MD600S-4T9R5B-INT

MD520-4T7.5B



Features:

- Ultra small volume rail type, space saving installation.
- Easy to use, fast debugging, and strong stability.
- High cost performance universal type.

Model	Specification
Three Phase 0.75 KW	MD605S-4T2R3
Three Phase 1.5 KW	MD605S-4T4R8
Three Phase 2.2 KW	MD605S-4T5R5B
Three Phase 4 KW	MD605S-4T9R5B
Single Phase 2.2KW	MD600S-2S010B



MD520-4T7.5B



Features:

- High-performance vector control with strong torque at zero speed.
- Multi-functional, suitable for various scenarios.
- High reliability, easy scalability, industrial-grade stability.

MD520-4T7.5B



Features:

- Compact and versatile, easy to debug.
- Intelligent stable drive.
- Global certification, high cost-effectiveness.

ITS7070SH-G Ethernet



Features:

- Dual Ethernet ports, RS485 dual serial ports.
- IP66 high protection, 7-inch high-definition.
- Domestic high cost-effectiveness.

Model	Specification
MD520-4T7.5B	7.5kw MD520 VFD
MD520-4T11B	11kw MD520 VFD
MD520-4T15B	15kw MD520 VFD
MD520-4T18.5	18.5kw MD520 VFD
MD520-4T22	22kw MD520 VFD
MD520-4T30	30kw MD520 VFD
MD520-4T37	37kw MD520 VFD
MD520-4T45	45kw MD520 VFD
MD520-4T55	55kw MD520 VFD
MD520-4T75	75kw MD520 VFD
MD520-4T90	90kw MD520 VFD
MD520-4T110	110kw MD520 VFD
MD520-4T132	132kw MD520 VFD
MD520-4T160	160kw MD520 VFD

Model	Specification
MD290 3PH 7.5KW	MD290T7.5G/11PB
MD290 3PH 11KW	MD290T11G/18.5PB
MD290 3PH 18KW	MD290T18.5G/22P
MD290 3PH 22KW	MD290T22G/30P
MD290 3PH 30KW	MD290T30G/37P
MD290 3PH 37KW	MD290T37G/45P
MD290 3PH 45KW	MD290T45G/55P
MD290 3PH 55KW	MD290T55G/75P
MD290 3PH 75KW	MD290T75G/90P
MD290 3PH 90KW	MD290T90G/110P
MD290 3PH 110KW	MD290T110G/132P
MD290 3PH 132KW	MD290T132G/160P
MD290 3PH 160KW	MD290T160G/200P

Model	Specification
ITS7070SH-G RS485	HMI 7inch with RS485
ITS7070SH-G Ethernet	HMI 7inch with Ethernet

